



# Prima Plus FD120 62mm

## Fire Rated Interior Grade Door Blanks

Halspan Prima Plus 120 internal fire door blanks feature Halspan's unique 3-layer particle board with additional mineral layer enhancement. Specifically designed for the purpose, using a complex combination of chemical and engineering development, these blanks produce doors of altogether superior quality, strength and overall performance, with the additional benefit of not having formaldehyde added to their construction.



### Fire Rating FD120

<b>Tested in Accordance with:</b>	BS 476: Part 22: 1987		
<b>Maximum Approved Sizes*</b> (Please check standard supplied sizes shown overleaf) * Maximum approved sizes based on timber door frames. Refer to test data for full details.	Single Doors	2400 x 1105mm	
		2640 x 1000mm	
	Double Doors	2400 x 1080mm	
		2590 x 1000mm	
<b>Approved Frames</b>	Timber Hardwood		
<b>Panel Effect</b>	No		
<b>Feature Grooves</b>	No		





### Acoustics

<b>Tested in Accordance with:</b>	BS EN ISO 10140-2:2010	
<b>Acoustic Performance</b>	Single Doors	Unglazed 34dB/Rw
	Double Doors	Unglazed 36dB/Rw



### Environmental



### General Properties

<b>Weight</b>	47 kg/m <sup>2</sup>
<b>Density (±10%)</b>	744 kg/m <sup>3</sup>
<b>Moisture Content</b>	Ex factory 6-10%




### Design Criteria

Stock Board Sizes	2200 x 930 mm 2390 x 1190 mm
Lipping Glue Lines	PU
Lipping Section Details	3 mm thick
Rebated Lippings (double doors etc)	Not Permitted
Standard Intumescent	Halspan Intumescent Kit

### Doorset Configurations



LSASD



LSADD



### Seals & Hardware



Seals



Hardware

Refer to relevant product third party scope data and literature for further information.

For technical guidance please contact the technical support team -

[technical@halspan.com](mailto:technical@halspan.com)